

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Steelman Security Seal
Other means of identification	Stock No. JSP10118
Recommended use	Special Industrial Finish
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	JS Products, Inc.
Address	6445 Monetessouri Street Las Vegas, NV 89113
Telephone	800-255-7701 Fax: 775-898-8773
Website	www.steelmantools.com
E-mail	customerservice@steelmantools.com
Emergency phone number	800-255-7011

2. Hazards Identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1B
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger	
Hazard statement	May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.	
Precautionary statement		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Take off contaminated clothing and wash before reuse. If exposed or concerned: Get medical advice/attention.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	Not applicable.	

3. Composition/Information on Ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Hydrous magnesium silicate		14807-96-6	5 - 10
2-Propanol, 1-butoxy-		5131-66-8	1 - 5
Dipropylene glycol monobutyl ether		29911-28-2	1 - 5
Titanium oxide		13463-67-7	1 - 5
1,2-Ethanediol		107-21-1	0.5 - 1.5
Crystalline silica		14808-60-7	0.1 - 1
Sodium nitrite		7632-00-0	0.1 - 1

Composition comments The exact % concentration of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA HCS 1910.1200.

4. First Aid Measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see product label). Take off contaminated clothing and wash before reuse.
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. If swallowed, call a Poison Control Center or doctor immediately for treatment advice.
Most important symptoms/effects, acute and delayed	Prolonged exposure may cause chronic effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Skin irritation. May cause redness and pain. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wash contaminated clothing before reuse. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Dry chemical. Water spray. Carbon dioxide. Foam.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use.
 Avoid contact with eyes, skin and clothing.
 Provide adequate ventilation.
 Do not breathe mist or vapor.
 Avoid contact during pregnancy/while nursing.

Do not handle until all safety precautions have been read and understood.
 Avoid prolonged exposure.
 Wear appropriate personal protective equipment.
 Observe good industrial hygiene practices.
 When using, do not eat, drink or smoke.
 Wash hands thoroughly after handling.
 Wash hands before breaks and immediately after handling the product.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container.
 Store away from incompatible materials (see Section 10 of the SDS).
 Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
Titanium oxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf 2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2-Ethanediol (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol.
Crystalline silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium oxide (CAS 13463-67-7)	TWA	10 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Crystalline silica (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Chemicals listed in section 3 that are not listed here do not have established limit values for ACGIH or OSHA PEL.

Appropriate engineering controls

Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment**Eye/face protection**

If contact is likely, safety glasses with side shields are recommended.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Thermal hazards

Not available.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Blue
Odor	Mild ammonia
Odor threshold	Not available.
pH	8.5 - 9
Melting point/freezing point	32 °F (0 °C)
Initial boiling point and boiling range	212 °F (100 °C)
Pour point	Not available.

Specific gravity	1.11
Partition coefficient (n-octanol/water)	Not available.
Flash point	> 212.0 °F (> 100.0 °C) Pensky-Martens Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and Reactivity

Reactivity	May react with incompatible materials.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Avoid heat, flames, sparks, and all other sources of ignition. Keep from freezing. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Skin irritation. May cause redness and pain. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components	Species	Test Results
1,2-EthanedioI (CAS 107-21-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	9500 mg/kg
<i>Inhalation</i>		
LC50	Rat	2725 mg/m ³ , 4 hr
<i>Oral</i>		
LD50	Cat	1650 mg/kg
	Dog	5500 mg/kg
	Guinea pig	6600 mg/kg
	Human	1110 - 1665 mg/kg

Components	Species	Test Results
	Mouse	7500 mg/kg
	Rabbit	5000 mg/kg
	Rat	5890 mg/kg
2-Propanol, 1-butoxy- (CAS 5131-66-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	3100 mg/kg
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	3300 mg/kg
Crystalline silica (CAS 14808-60-7)		
Acute		
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	500 mg/kg
Dipropylene glycol monobutyl ether (CAS 29911-28-2)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	3700 mg/kg
Hydrous magnesium silicate (CAS 14807-96-6)		
Acute		
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Not available	
Sodium nitrite (CAS 7632-00-0)		
Acute		
<i>Inhalation</i>		
LC50	Rat	5.5 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	175 mg/kg
	Rabbit	186 mg/kg
	Rat	88 mg/kg
		85 mg/kg
Titanium oxide (CAS 13463-67-7)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	24000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	

Serious eye damage/eye irritation	Causes serious eye irritation.
Corneal opacity value	Not available.
Iris lesion value	Not available.
Conjunctival reddening value	Not available.
Conjunctival oedema value	Not available.
Recover days	Not available.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Non-hazardous by OSHA criteria.

Contains < 3% (w/w) DMSO-extract

The components listed below are inextricably bound and not biologically available.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (CAS 14808-60-7)	1 Carcinogenic to humans.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	1 Carcinogenic to humans.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	1 Carcinogenic to humans.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	1 Carcinogenic to humans.
Hydrous magnesium silicate (CAS 14807-96-6)	2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
Titanium oxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline silica (CAS 14808-60-7)	Known To Be Human Carcinogen.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Known To Be Human Carcinogen.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Known To Be Human Carcinogen.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	Known To Be Human Carcinogen.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs (Kidneys) through prolonged or repeated exposure.
Aspiration hazard	Not classified.
Chronic effects	May cause damage to organs through prolonged or repeated exposure.
Further information	Not available.

12. Ecological Information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. See below

Components	Species	Test Results
1,2-Ethanediol (CAS 107-21-1)		
Crustacea	EC50 Daphnia	46300 mg/L, 48 Hours
Aquatic		
Fish	LC50 Fathead minnow (Pimephales promelas)	8050 mg/l, 96 hours
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Crustacea	EC50 Daphnia	1000 mg/L, 48 Hours

Components	Species		Test Results	
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Sodium nitrite (CAS 7632-00-0)	Aquatic			
	Crustacea	EC50	Greasyback shrimp (Metapenaeus ensis)	16.14 - 26.61 mg/l, 48 hours
	Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.15 - 0.25 mg/l, 96 hours
Titanium oxide (CAS 13463-67-7)	Aquatic			
	Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
	Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octanol / water (log Kow)			
1,2-Ethanediol			-1.36
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

U.S. Department of Transportation (DOT)	Not regulated as dangerous goods.
Transportation of Dangerous Goods (TDG - Canada)	Not regulated as dangerous goods.
IATA/ICAO (Air)	Not regulated as dangerous goods.
IMDG (Marine Transport)	Not regulated as dangerous goods.

15. Regulatory Information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)		
Sodium nitrite (CAS 7632-00-0)		1.0 % One-Time Export Notification only.
CERCLA Hazardous Substance List (40 CFR 302.4)		
1,2-Ethanediol (CAS 107-21-1)		Listed.

Sodium nitrite (CAS 7632-00-0)

Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2-Ethanediol	107-21-1	0.5 - 1.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,2-Ethanediol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Hazardous Substances (Director's): Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Listed.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
Hydrous magnesium silicate (CAS 14807-96-6) Listed.
Sodium nitrite (CAS 7632-00-0) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline silica (CAS 14808-60-7) Listed.
Titanium oxide (CAS 13463-67-7) Listed.

US - Illinois Chemical Safety Act: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Sodium nitrite (CAS 7632-00-0) Listed.

US - Louisiana Spill Reporting List: Reportable quantity (total mass into atmosphere)

1,2-Ethanediol (CAS 107-21-1) 5000 LBS

US - Louisiana Spill Reporting: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Sodium nitrite (CAS 7632-00-0) Listed.

US - Minnesota Haz Subs: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Crystalline silica (CAS 14808-60-7) Listed.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Listed.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
Hydrous magnesium silicate (CAS 14807-96-6) Listed.
Titanium oxide (CAS 13463-67-7) Listed.

US - New Jersey RTK - Substances: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
Crystalline silica (CAS 14808-60-7) Listed.

Hydrous magnesium silicate (CAS 14807-96-6) Listed.
 Sodium nitrite (CAS 7632-00-0) Listed.
 Titanium oxide (CAS 13463-67-7) Listed.

US - New York Release Reporting: Hazardous Substances: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
 Sodium nitrite (CAS 7632-00-0) Listed.

US - Texas Effects Screening Levels: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.
 2-Propanol, 1-butoxy- (CAS 5131-66-8) Listed.
 Crystalline silica (CAS 14808-60-7) Listed.
 Dipropylene glycol monobutyl ether (CAS 29911-28-2) Listed.
 Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Listed.
 Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Listed.
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.
 Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
 Hydrous magnesium silicate (CAS 14807-96-6) Listed.
 Sodium nitrite (CAS 7632-00-0) Listed.
 Titanium oxide (CAS 13463-67-7) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

1,2-Ethanediol (CAS 107-21-1) Listed.

US. Massachusetts RTK - Substance List

1,2-Ethanediol (CAS 107-21-1) Listed.
 Crystalline silica (CAS 14808-60-7) Listed.
 Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Listed.
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.
 Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
 Hydrous magnesium silicate (CAS 14807-96-6) Listed.
 Sodium nitrite (CAS 7632-00-0) Listed.
 Titanium oxide (CAS 13463-67-7) Listed.

US. Pennsylvania RTK - Hazardous Substances

1,2-Ethanediol (CAS 107-21-1) Listed.
 Crystalline silica (CAS 14808-60-7) Listed.
 Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8) Listed.
 Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Listed.
 Hydrous magnesium silicate (CAS 14807-96-6) Listed.
 Sodium nitrite (CAS 7632-00-0) Listed.
 Titanium oxide (CAS 13463-67-7) Listed.

US. Rhode Island RTK

1,2-Ethanediol (CAS 107-21-1) Listed.
 Sodium nitrite (CAS 7632-00-0) Listed.


Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

26-May-2015

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Prepared by

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021